

10-123 A hot plate is to be cooled by attaching aluminum pin fins on one side. The rate of heat transfer from the 1 m by 1 m section of the plate and the effectiveness of the fins are to be determined.

Assumptions 1 Steady operating conditions exist. 2 The temperature along the fins varies in one direction only (normal to the plate). 3 Heat transfer from the fin tips is negligible. 4 The heat transfer coefficient is constant and uniform over the entire fin surface. 5 The thermal properties of the fins are constant. 6 The heat transfer coefficient accounts for the effect of radiation from the fins.

Properties The thermal conductivity of the aluminum plate and fins is given to be $k = 237 \text{ W/m}\cdot^\circ\text{C}$.

Analysis Noting that the cross-sectional areas of the fins are constant, the efficiency of the circular fins can be determined to be

$$m = \sqrt{\frac{hp}{kA_c}} = \sqrt{\frac{h\pi D}{k\pi D^2/4}} = \sqrt{\frac{4h}{kD}} = \sqrt{\frac{4(35 \text{ W/m}^2\cdot^\circ\text{C})}{(237 \text{ W/m}\cdot^\circ\text{C})(0.0025 \text{ m})}} = 15.37 \text{ m}^{-1}$$

$$\eta_{\text{fin}} = \frac{\tanh mL}{mL} = \frac{\tanh(15.37 \text{ m}^{-1} \times 0.03 \text{ m})}{15.37 \text{ m}^{-1} \times 0.03 \text{ m}} = 0.935$$

The number of fins, finned and unfinned surface areas, and heat transfer rates from those areas are

$$n = \frac{1 \text{ m}^2}{(0.006 \text{ m})(0.006 \text{ m})} = 27,777$$

$$A_{\text{fin}} = 27777 \left[\pi DL + \frac{\pi D^2}{4} \right] = 27777 \left[\pi(0.0025)(0.03) + \frac{\pi(0.0025)^2}{4} \right] = 6.68 \text{ m}^2$$

$$A_{\text{unfinned}} = 1 - 27777 \left(\frac{\pi D^2}{4} \right) = 1 - 27777 \left[\frac{\pi(0.0025)^2}{4} \right] = 0.86 \text{ m}^2$$

$$\begin{aligned} \dot{Q}_{\text{finned}} &= \eta_{\text{fin}} \dot{Q}_{\text{fin,max}} = \eta_{\text{fin}} h A_{\text{fin}} (T_b - T_\infty) \\ &= 0.935(35 \text{ W/m}^2\cdot^\circ\text{C})(6.68 \text{ m}^2)(100 - 30)^\circ\text{C} \\ &= 15,300 \text{ W} \end{aligned}$$

$$\begin{aligned} \dot{Q}_{\text{unfinned}} &= h A_{\text{unfinned}} (T_b - T_\infty) = (35 \text{ W/m}^2\cdot^\circ\text{C})(0.86 \text{ m}^2)(100 - 30)^\circ\text{C} \\ &= 2107 \text{ W} \end{aligned}$$

Then the total heat transfer from the finned plate becomes

$$\dot{Q}_{\text{total,fin}} = \dot{Q}_{\text{finned}} + \dot{Q}_{\text{unfinned}} = 15,300 + 2107 = 1.74 \times 10^4 \text{ W} = \mathbf{17.4 \text{ kW}}$$

The rate of heat transfer if there were no fin attached to the plate would be

$$\begin{aligned} A_{\text{no fin}} &= (1 \text{ m})(1 \text{ m}) = 1 \text{ m}^2 \\ \dot{Q}_{\text{no fin}} &= h A_{\text{no fin}} (T_b - T_\infty) = (35 \text{ W/m}^2\cdot^\circ\text{C})(1 \text{ m}^2)(100 - 30)^\circ\text{C} = 2450 \text{ W} \end{aligned}$$

Then the fin effectiveness becomes

$$\varepsilon_{\text{fin}} = \frac{\dot{Q}_{\text{fin}}}{\dot{Q}_{\text{no fin}}} = \frac{17,400}{2450} = \mathbf{7.10}$$

